



Service-Information

Cust. Serv. - Techn. Dept. VKT	er/lü/wi/fm	Motorcycles R50, R60, R69S, R27 Grp: Springs & Shock Absorbers	Munich, 18 June 1964 Nr. 1/64 (212) en.
-----------------------------------	-------------	---	--

Re: Lubrication of the Front Wheel-Swinging Arm Bearing

Dear Sirs,

By the introduction as standard equipment of a funnel-type grease fitting (nipple) for the lubrication of the front wheel swinging arm bearing commencing with frame Nr.

636 591 (R 50)

626 361 (R 60)

658 624 (R 69 S)

382 853 (R 27)

the maintenance of this bearing has been simplified considerably.

If the customer wishes, this funnel-type grease fitting may subsequently be installed (against charge) on the front wheel swinging arm for the lubrication of the bearing, on the models R 26, R 27, R 50, R 50 S, R 60, and R 69 S.

The following parts are necessary for this:

<u>Description of Part</u>	<u>Part Nr.</u>
1 Funnel-type grease fitting	99 60 270
2 Flat washers	10 20 136
2 Seal rings	20 00 331

Parts superseded:

2 Seal rings	20 00 330
2 Flat washers	20 00 322

For the installation, to which the following guidelines pertain, we refer to the Repair Manual R 50, R 50 S, R 60, and R 69 S, from which the corresponding installing operations may be perceived.

Kennntnis genommen	Betriebsleitung	Werkstatt	KD-Annahme	Gewährleistungs- Sachbearbeiter	E-Teildienst	Ablage	Betriebsleitung Werkstatt
-----------------------	-----------------	-----------	------------	------------------------------------	--------------	--------	------------------------------